



STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 130.00 lm/W			
MODEL	ZGSM-SDD100H5	I _{max} (cd)	5131	η street_up(%)	0.0
NOMINAL POWER(W)	100	LOR(%)	100.0	η street_down(%)	51.5
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	13000	η house_up(%)	0.0
NOMINAL FLUX(lm)	13000	MAXIMUM @(C,γ)	15,38.0	η house_down(%)	48.6
LAMPS INSIDE	1	η up(%)	0.0	76 FLASHAREA(m2)	0.05000
TEST VOLTAGE(V)	220.1	η down(%)	100.0	SLI	20.992


INTENSITY DISTRIBUTION DIAGRAM
IN C PLANSMAX INTENSITY CONE SURFACE
DISTRIBUTION DIAGRAM

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:



Classification:



IES:Type V - Very Short
 CIE:Narrow - Short
 IES:Full cut-off
 CIE:Full cut-off
 Max.At80:21.93cd/klm
 Max.At90:0cd/klm
 Max.80-90:21.93cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
I _{max} =100%	5131
90%	4618
80%	4105
70%	3591
60%	3078
50%	2565
40%	2052
30%	1539
20%	1026
10%	513
5%	257

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

COEFFICIENT OF UTILIZATION CURVE AND ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.480m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	Φ lum,lamp
10	4152	4126	4067	3991	4029	4011	4039	4057	0- 10	383.0	383.0	2.95,2.95
20	4385	4301	4184	4120	4169	4124	4154	4239	10- 20	1169	1552	11.9,11.9
30	4763	4596	4374	4284	4289	4271	4359	4618	20- 30	1994	3547	27.3,27.3
40	5066	5022	4793	4413	4353	4343	4542	4762	30- 40	2888	6435	49.5,49.5
50	3881	3986	3826	3306	3176	3170	3442	3616	40- 50	3281	9715	74.7,74.7
60	1546	1533	1243	1112	1083	931.2	883.1	1154	50- 60	2094	11809	90.8,90.8
70	562.2	537.6	449.5	510.2	533.2	494.4	407.7	486.0	60- 70	707.2	12516	96.3,96.3
80	227.6	265.4	193.9	229.7	202.0	200.2	73.00	215.5	70- 80	387.1	12903	99.3,99.3
90	0	0	0	0	0	0	0	0	80- 90	97.23	13000	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM


NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.480m [K=1.0000]
 Remarks:

LCS REPORT

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:

LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH


C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

BUG REPORT

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:

IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	1780.6	13.7
FM - Front-Medium(30-60)	4270	32.8
FH - Front-High(60-80)	581.22	4.5
FVH - Front-Very High(80-90)	56.871	0.4
Total Forward Light	6688.7	51.4

BL - Back-Low(0-30)	1766	13.6
BM - Back-Medium(30-60)	3992.3	30.7
BH - Back-High(60-80)	513.09	3.9
BVH - Back-Very High(80-90)	40.355	0.3
Total Back Light	6311.8	48.6

UL - Uplight-Low(90-100)	0	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0	0.0

BUG(Back,Up,Glare) Rating	B3-U0-G1
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	6311.8	0	6311.8
Street Side	6688.7	0	6688.7


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ROAD ISOCANDELA REPORT

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```