



STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 160.00 lm/W			
MODEL	ZGSM-SDD50H5	I _{max} (cd)	3316	η street_up(%)	0.0
NOMINAL POWER(W)	50	LOR(%)	100.0	η street_down(%)	50.5
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	8000	η house_up(%)	0.0
NOMINAL FLUX(lm)	8000	MAXIMUM @(C,γ)	180,35.0	η house_down(%)	49.5
LAMPS INSIDE	1	η up(%)	0.0	76 FLASHAREA(m2)	0.05000
TEST VOLTAGE(V)	220.1	η down(%)	100.0	SLI	18.621




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:



Classification:



IES:Type V - Very Short
 CIE:Narrow - Short
 IES:Full cut-off
 CIE:Full cut-off
 Max.At80:8.041cd/klm
 Max.At90:0cd/klm
 Max.80-90:8.041cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
Imax=100%	3316
90%	2984
80%	2653
70%	2321
60%	1990
50%	1658
40%	1326
30%	995
20%	663
10%	332
5%	166

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

COEFFICIENT OF UTILIZATION CURVE AND ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.480m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	Φ lum,lamp
10	3061	3046	3038	3028	3072	3039	3013	3000	0- 10	289.5	289.5	3.62,3.62
20	3035	3046	3066	3047	3078	3031	2999	2973	10- 20	858.1	1148	14.3,14.3
30	3083	3155	3231	3212	3240	3162	3090	3027	20- 30	1422	2569	32.1,32.1
40	3116	3132	3120	3135	3172	3131	3060	3056	30- 40	2000	4569	57.1,57.1
50	2145	2113	2115	2108	2148	2077	2071	2091	40- 50	2080	6649	83.1,83.1
60	261.1	318.9	353.9	357.0	302.0	276.2	273.7	288.0	50- 60	1042	7692	96.2,96.1
70	100.9	128.1	117.9	124.7	114.8	116.9	106.2	119.7	60- 70	184.9	7877	98.5,98.5
80	45.79	57.78	60.84	59.35	46.28	58.24	58.43	56.54	70- 80	85.03	7962	99.5,99.5
90	0	0	0	0	0	0	0	0	80- 90	37.79	8000	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM


NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.480m [K=1.0000]
Remarks:

LCS REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:

LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH


C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

BUG REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:

IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	1292.9	16.2
FM - Front-Medium(30-60)	2586.9	32.3
FH - Front-High(60-80)	140.41	1.8
FVH - Front-Very High(80-90)	18.972	0.2
Total Forward Light	4039.2	50.5

BL - Back-Low(0-30)	1276.5	16.0
BM - Back-Medium(30-60)	2535.5	31.7
BH - Back-High(60-80)	129.55	1.6
BVH - Back-Very High(80-90)	18.82	0.2
Total Back Light	3960.3	49.5

UL - Uplight-Low(90-100)	0	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0	0.0

BUG(Back,Up,Glare) Rating	B3-U0-G1
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	3960.3	0	3960.3
Street Side	4039.2	0	4039.2


C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ROAD ISOCANDELA REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```