



STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 160.00 lm/W			
MODEL	ZGSM-SDD150H5	Imax(cd)	9949	$\eta$ street_up(%)	0.0
NOMINAL POWER(W)	150	LOR(%)	100.0	$\eta$ street_down(%)	50.5
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	24000	$\eta$ house_up(%)	0.0
NOMINAL FLUX(lm)	24000	MAXIMUM @(C, $\gamma$ )	180,35.0	$\eta$ house_down(%)	49.5
LAMPS INSIDE	1	$\eta$ up(%)	0.0	76 FLASHAREA(m2)	0.05000
TEST VOLTAGE(V)	220.1	$\eta$ down(%)	100.0	SLI	20.201




C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:



Classification:



IES:Type V - Very Short  
 CIE:Narrow - Short  
 IES:Full cut-off  
 CIE:Full cut-off  
 Max.At80:8.042cd/klm  
 Max.At90:0cd/klm  
 Max.80-90:8.042cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
Imax=100%	9949
90%	8954
80%	7959
70%	6964
60%	5969
50%	4974
40%	3980
30%	2985
20%	1990
10%	995
5%	497

C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

# COEFFICIENT OF UTILIZATION CURVE AND ISOLUX DIAGRAM



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 $\gamma$  Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.480m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:


$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	$\Phi$ lum,lamp
10	9183	9137	9113	9084	9218	9117	9038	9001	0- 10	868.4	868.4	3.62,3.62
20	9107	9138	9198	9143	9235	9094	8998	8919	10- 20	2575	3443	14.3,14.3
30	9249	9465	9693	9636	9722	9486	9270	9082	20- 30	4266	7709	32.1,32.1
40	9350	9397	9361	9407	9515	9394	9181	9168	30- 40	6001	13709	57.1,57.1
50	6436	6338	6347	6325	6443	6232	6214	6274	40- 50	6240	19949	83.1,83.1
60	783.3	956.7	1062	1071	906.0	828.6	821.1	864.0	50- 60	3127	23077	96.2,96.2
70	302.7	384.3	353.7	374.2	344.3	350.6	318.5	359.2	60- 70	554.8	23632	98.5,98.5
80	137.4	173.3	182.5	178.1	138.9	174.7	175.3	169.6	70- 80	255.1	23887	99.5,99.5
90	0	0	0	0	0	0	0	0	80- 90	113.4	24000	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

**ISOCANDELA DIAGRAM**


NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

## Planar Illuminance Curve




C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: DAMIN  
 Test Date: 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity: 65.0%  
 Test Distance: 10.480m [K=1.0000]  
 Remarks:

**LCS REPORT**

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:

**LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH**


C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

### BUG REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:

#### IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	3878.9	16.2
FM - Front-Medium(30-60)	7761.2	32.3
FH - Front-High(60-80)	421.25	1.8
FVH - Front-Very High(80-90)	56.919	0.2
Total Forward Light	12118	50.5

BL - Back-Low(0-30)	3829.6	16.0
BM - Back-Medium(30-60)	7607	31.7
BH - Back-High(60-80)	388.69	1.6
BVH - Back-Very High(80-90)	56.463	0.2
Total Back Light	11882	49.5

UL - Uplight-Low(90-100)	0	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0	0.0

BUG(Back,Up,Glare) Rating	B4-U0-G1
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	11882	0	11882
Street Side	12118	0	12118

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018


γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:



ROAD ISOCANDELA REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```